

Diamex®

Applications

Commercial
Industrial
Parks
Schools
Security

Features

Hard to climb
Difficult to cut through
High delay factor
Good visibility
Cost effective
Many options for tops

Specification

Standard heights: 1800, 2000, 2400 and 3000mm.

Posts: 102x44 RSJ at 2750 post centres. Prestige: Box section posts. Centres and size of post dependent on fence height.

Vertical: 25x25 SHS set diamond to view to give a maximum gap of 100mm.

Horizontal Rails: Heavy duty rolled steel channel. Up to 2400mm high - 2 (No), 3000mm high - 3 (No).

Fixings: Domed headed bolts, permacone security fixings and special angle cleats which allow the panels to be stepped 0-35mm and 85-123mm on site.

Toppings:

Finials, pressed steel spear or angled tops

Finish:

Hot Dip Galvanised to BS EN ISO 1461 or Galvanised & Polyester Powder Coated.



Diamex® Fencing provides a strong and aesthetically pleasing perimeter fence suitable for most requirements. Efficient manufacturing processes ensure that Diamex® Fencing is long lasting and affordable.



Matrix Fencing Systems Ltd

PO Box 4115, Bath BA1 0FN Tel: 01225 830119 Fax: 01225 830755

Mob: 07540 724715 www.matrixfencing.co.uk

sales@matrixfencing.co.uk Contact: James Sanders

